



# Spun Aluminum Exhausters

**ALX-UD & ALX-DD**  
Direct Drive Series

**ALX-UB & ALX-DB**  
Belt Drive Series

**NEW with EC MOTORS**  
**ALX-UD-EC & ALX-DD-EC**  
Direct Drive  
Series

**ALSO  
AVAILABLE  
WITH**

**EC MOTORS**  
for energy savings

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.



## WARRANTY

Canarm Air Moving Products are guaranteed for a period of one year against manufacturing defects in material and workmanship when operating under normal conditions. Liability is limited to the replacement of defective parts. Labour and transportation costs are not included.

If a replacement is warranted the following MUST be provided:

1. Model of equipment
2. Date of manufacture
3. Original invoice reference number(s)

## CANARM LTD.

*Corporate Office / HVAC Manufacturing Facility*

2157 Parkedale Ave., PO Box 367  
Brockville, ON N4B 2Z3 Canada

Tel: 613-342-5424

Fax: 800-263-4598


[www.canarm.com](http://www.canarm.com)

[hvacsales@canarm.ca](mailto:hvacsales@canarm.ca)

# ALX105-UD

Max RPM - 1800  
HP - 1/3

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX105-UD013V operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX120-UD

Max RPM - 1800  
HP - 1/2

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX120-UD033V operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX135-UD

Max RPM - 1800  
HP - 3/4

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX135-UD075V operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX150-UD

Max RPM - 1800  
HP - 1  
Single Speed




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX150-UD075S operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX165-UD

Max RPM - 1800  
 HP - 2  
 Single Speed

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX165-UD150S operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX135-UB

Max RPM - 1800  
Max HP - 3/4  
Shaft Size - 3/4"

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX150-UB

Max RPM - 1800  
Max HP - 1  
Shaft Size - 3/4"



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX165-UB

**Max RPM - 1800**  
**Max HP - 2**  
**Shaft Size - 3/4"**

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX180-UB

**Max RPM - 1500**  
**Max HP - 2**  
**Shaft Size - 3/4"**


Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX210-UB

Max RPM - 1300  
Max HP - 3  
Shaft Size - 1"




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

# ALX245-UB

Max RPM - 1200  
Max HP - 5  
Shaft Size - 1"



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

# ALX105-DD

Max RPM - 1800  
HP - 1/3

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX105-DD013V operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX120-DD

Max RPM - 1800  
HP - 1/2

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).


ALX120-DD033V operates at 1650 RPM. Curve shown beyond this point for reference.



# ALX135-DD

Max RPM - 1800  
HP - 3/4

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX135-DD075V operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX150-DD

Max RPM - 1800  
HP - 1  
Single Speed




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX150-DD075S operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX165-DD

**Max RPM - 1800  
HP - 2  
Single Speed**

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

ALX165-DD150S operates at 1650 RPM. Curve shown beyond this point for reference.

# ALX135-DB

Max RPM - 1800  
Max HP - 3/4  
Shaft Size - 3/4"

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX150-DB

Max RPM - 1800  
Max HP - 1  
Shaft Size - 3/4"

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX165-DB

Max RPM - 1800  
Max HP - 2  
Shaft Size - 3/4"

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX180-DB

Max RPM - 1500  
Max HP - 2  
Shaft Size - 3/4"


Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX210-DB

Max Wheel RPM - 1300  
Max HP - 3  
Shaft Size - 1"




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

# ALX245-DB

Max Wheel RPM - 1200  
Max HP - 5  
Shaft Size - 1"



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

# ALX105-UD-EC

Max RPM - 1800  
HP - 1/3

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX120-UD-EC

Max RPM - 1800  
HP - 1/3


Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX135-UD-EC

Max RPM - 1800  
HP - 3/4




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX150-UD-EC

Max RPM - 1800  
HP - 1




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX165-UD-EC

Max RPM - 1500  
HP - 1

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).



# ALX180-UD-EC

Max RPM - 1200  
HP - 1

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX210-UD-EC

Max RPM - 900  
HP - 1

Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX105-DD-EC

Max RPM - 1800  
HP - 1/3



Static Pressure  
(in H<sub>2</sub>O)



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.


Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX120-DD-EC

Max RPM - 1800  
HP - 1/2



Static Pressure  
(in H<sub>2</sub>O)



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.


Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX135-DD-EC

Max RPM - 1800  
HP - 1



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.




Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX150-DD-EC

Max RPM - 1800  
HP - 1




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.



Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX165-DD-EC

Max RPM - 1475  
HP - 1




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX180-DD-EC

Max RPM - 1200  
HP - 1




Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).

# ALX210-DD-EC

Max RPM - 900  
HP - 1



Canarm certifies that the ALX Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.

Performance certified is for installation type A- Free Inlet , Free outlet, Power rating (HP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories).



[WWW.CANARM.COM](http://WWW.CANARM.COM)  
[HVACSALES@CANARM.CA](mailto:HVACSALES@CANARM.CA)