

LED

4" Recessed Downlight

DL-4-9YC-WH-C

CANARM LTD.

PO Box 367, 2157 Parkedale Avenue, Brockville, Ontario K6V5V6

Tel: 613-342-5424 | Fax: 1-800-263-4598

2555 Rue Bernard Lefebvre, Laval, Quebec H7C 0A5

Tel: 1-450-665-2535 | Fax: 1-450-665-0910

808 Commerce Park Drive, Ogdensburg, New York, USA 13669

Tel: 1-800-267-4427 | Fax: 1-800-263-4598

www.canarm.com

General

Size of Fixture: 5.12" W x 5.12" H x 2.09" D

Finish: white

Gimbal trim, Acrylic lens

IC Rated, Driverless, 120 Volt, 9W

Lumens: 500 lumens thru the lens, Dimmable

Beam spread: 120°

Bulb Life: 50,000 hours

CRI: 90

Colour Temperature: 3000K

Starting Minimum Temperature: -40°C

Compatible dimmers: LEVITON #742-6672-HLW,
LEVITON #722-6674-PDW, LUTRON #SCL-153PH-WH

Recessed mounted, J-Box included

Max.# of lamps per 150W dimmer: 16 pcs

Cut-out template: 4 3/8"

Available 24" rough in plate: IPLED-SR-C



Packaging

Colour box 6.65" x 5.39" x 2.83" (169 x 137 x 72mm)

Colour box weight: 0.70 lbs

Master box: 13.98" x 11.61" x 15.16" (355 x 295 x 385mm)

Pieces per Master box: 20

Master box weight: 15.61 lbs

Warranty & Safety Standards

Warranty: LED Module-Limited 5 year

Fixture-Limited 1 year

cETLus rated

Energy Star Rated

Suitable for wet locations

Indoor/Outdoor enclosed use



WARNING: The use of this product can expose you to chemicals including Cadmium, which is known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Prepared for
Contact
Date
Presented by
Remarks