

PBKD / WMKD - COMMERCIAL CIRCULATING FANS

Canarm/LFI's high velocity commercial fans economically provide relief from summer heat by creating a gentle air movement. Pedestal type fans come with a sturdy base and adjustable pole. All fans have a 3 speed motor with industrial grade aluminum blades.

FEATURES

- · Commercial duty circulating fans (Knock Down).
- · Painted aluminum blades.
- · Standard OSHA guard.
- · Motors are thermally protected.
- · Available in 24" and 30" stationary and oscillating models.
- · Packaged in one box, complete with mounting accessories.
- · Complete with 10', 120V grounded plug.

PERFORMANCE SPECIFICATIONS

FAN SIZE	MODE	& WEIGHT (LBS)						
	PEDESTAL FAN	WEIGHT (LBS)	WALL MOUNT FAN	WEIGHT (LBS)	DESCRIPTION	H.P.	SUPPLY CFM	CFM/W
24"	PBKD24-3SP	74	WMKD24-3SP	38	3 Speed	1/4	7805/7403/6774	43.2 / 41.7 / 36.2
24"	PBKD24-OSC	78	WMKD24-OSC	42	3 Speed Oscillating	1/4	7805/7403/6774	43.2 / 41.7 / 36.2
30"	PBKD30-3SP	80	WMKD30-3SP	46	3 Speed	1/4	10205 / 9855 / 9447	57.4 / 51.5 / 45.3
30"	PBKD30-OSC	84	WMKD30-OSC	49	3 Speed Oscillating	1/4	10205 / 9855 / 9447	57.4 / 51.5 / 45.3

CCU - COMMERCIAL CIRCULATING FANS

Canarm/LFI's high velocity commercial fans economically provide relief from summer heat by creating a gentle air movement. Pedestal type fans come with a sturdy base and adjustable pole. All fans have a 3 speed motor with industrial grade aluminum blades.

FEATURES

- · Commercial duty circulating fans (Knock Down).
- 20" stationary models.
- Adjustable pedestal (54"-64").
- · 3 speeds.
- · Painted aluminum blades.
- Standard OSHA guard.
- · Motors are thermally protected.
- Complete with 10', 120V grounded plug.
- 20" pedestal complete with wheel kit.

PERFORMANCE SPECIFICATIONS

N	IODEL	FAN SIZE	DESCRIPTION	HP	SUPPLY CFM	CFM/W	WEIGHT (lbs)
С	CUP20	20"	3 Speed Pedestal Fan	1/4	5513/4681/3918	28.0 / 27.3 / 25.2	47

