

UTILITY EXHAUST FANS

Ideal for garage exhaust, residential greenhouses, workshops and any other larger residential rooms requiring an exhaust fan.



FRONT VIEW

UF10-G

The UF10-G has a robust appearance. It comes in a grey finish and with a 10' black cord and grounded plug.



BACK VIEW

FEATURES

- 10" utility fan
- Grey and black finish
- Single speed
- 14" chrome on/off pull chain
- Shipped completely assembled
- 120 volt, 10' black cord & SJT plug with ground
- The UF10-G changes the air in a 10' (3m) x 10' (3m) room every 2.5 minutes provided an adequate air inlet is available.

PERFORMANCE SPECIFICATIONS

MODEL	FAN SIZE	SPEED	CFM	AMPS (FLA)	VOLTS	WATTS	DIMENSIONS (mm)		WEIGHT (LBS)
							FRAMING	CARTON	
UF10-G	10"	Single	350	0.36	120	40	295 x 295	389 x 206 x 389	7

INSTALLATION

For the greatest efficiency, mount the fan as high as possible. Installation is fast and simple. The fan comes fully assembled. A sturdy 295 mm x 295 mm framed wall opening should be prepared in advance. Carefully pull the guard off of the fan unit. Carefully pull the orifice plate off of the fan unit. Insert the fan unit into the frame. Using wood screws for wooden frames or nut, bolt and lock washers for steel frames, secure the fan using the mounting holes provided. The shutters should be situated to close by gravity (The shutters will open up and out when the fan is running and will close by gravity when the fan is stopped). Carefully replace the orifice plate and then the guard (these should snap back into place). Plug the fan into a 120 volt household outlet. Use the pull chain to turn the fan on and off.

